

# Public Variables list

The environment-specific configuration functionality available for Aras Enterprise customers working with containerized deployments supports the list of Public Variables. These public variables can be used in transformations without adding a variable to Variable Groups as their values are automatically added during deployment. See the list of supported public variables below:

- ARAS\_AGENT\_REPLICATION\_STATUS
- ARAS\_AGENT\_REPLICATION\_INTERVAL
- ARAS\_AGENT\_REPLICATION\_MAX\_BATCH
- ARAS\_AGENT\_REPLICATION\_MAX\_PENDING
- ARAS\_AGENT\_REPLICATION\_TIMEOUT
- ARAS\_AGENT\_REPLICATION\_USER
- ARAS\_AGENT\_LoggerConfiguration\_\_MinimumLevel
- ARAS\_AGENT\_AgentService\_\_InnovatorServerUrl
- ARAS\_INNOVATOR\_INSTANCE\_NAME
- ARAS\_INNOVATOR\_CLIENT\_ORIGIN
- ARAS\_INNOVATOR\_CLIENT
- ARAS\_INNOVATOR\_CLIENT\_INTERNAL
- ARAS\_INNOVATOR\_CLIENT\_SERVER
- ARAS\_INNOVATOR\_DEPLOYMENT\_NAME
- ARAS\_INNOVATOR\_SERVER
- ARAS\_INNOVATOR\_SERVER\_INTERNAL
- ARAS\_INNOVATOR\_VAULT\_SERVER\_INTERNAL
- ARAS\_INNOVATOR\_CONVERSION\_SERVER
- ARAS\_INNOVATOR\_VAULT\_SERVER
- ARAS\_INNOVATOR\_OAUTH\_SERVER
- ARAS\_INNOVATOR\_OAUTH\_SERVER\_INTERNAL
- ARAS\_INNOVATOR\_AGENT\_SERVICE
- ARAS\_INNOVATOR\_TRANSIENT\_ERROR\_NUMBERS
- ARAS\_INNOVATOR\_SERVER\_METHOD\_ASSEMBLY\_CACHE\_EXPIRATION
- ARAS\_CLIENT
- ARAS\_CLIENT\_REDIS\_CONNECTION\_STRING
- ARAS\_CLIENT\_REDIS\_KEY\_PREFIX



- ARAS\_CLIENT\_DATA\_PROTECTION\_KEY\_LIFETIME
- ARAS\_CLIENT\_LoggerConfiguration\_\_MinimumLevel
- ARAS\_OAUTH\_CERTIFICATE\_PASSWORD
- ARAS\_OAUTH\_BASE\_PATH
- ARAS\_OAUTH\_LoggerConfiguration\_\_MinimumLevel
- ARAS\_OAUTH\_DATA\_PROTECTION\_KEY\_LIFETIME
- ARAS\_OAUTH\_REDIS\_CONNECTION\_STRING
- ARAS\_OAUTH\_REDIS\_KeyPrefix
- ARAS\_SERVER\_MAIL\_DELIVERYMETHOD
- ARAS\_SERVER\_SMTP\_SERVER
- ARAS\_SERVER\_SMTP\_PORT
- ARAS\_SERVER\_SMTP\_SSL
- ARAS\_SERVER\_SMTP\_USERNAME
- ARAS\_SERVER\_SMTP\_PASSWORD
- ARAS\_SERVER\_DATABASES
- ARAS\_SERVER\_ACCESSCONTROLMAXAGE
- ARAS\_SERVER\_ACCESSCONTROLEXPOSEHEADERS
- ARAS\_SERVER\_ACCESSCONTROLALLOWORIGIN
- ARAS\_SERVER\_INITIALIZE\_DATABASES\_ON\_STARTUP
- ARAS\_SERVER\_LoggerConfiguration\_\_MinimumLevel
- ARAS\_SERVER\_Tracing\_\_Instrumentation\_\_SqlClient\_\_Enabled
- ARAS\_SERVER\_VAULT\_REQUEST\_TIMEOUT
- ARAS\_SERVER\_REDIS\_CONNECTION\_STRING
- ARAS\_SERVER\_REDIS\_KEY\_PREFIX
- ARAS\_SERVER\_REDIS\_RETRY\_BACKOFF\_MILLISECONDS
- ARAS\_SERVER\_REDIS\_PREVENT\_THREAD\_THEFT
- ARAS\_SERVER\_DATA\_PROTECTION\_KEY\_LIFETIME
- ARAS\_SERVER\_INITIALIZE\_DATABASES\_ON\_STARTUP\_TIMEOUT\_SECONDS
- ARAS\_SERVER\_REPORT\_SERVER
- ARAS\_SERVER\_MSGRAPHAPICLIENT\_TENANTID
- ARAS\_SERVER\_MSGRAPHAPICLIENT\_CLIENTID
- ARAS\_SERVER\_MSGRAPHAPICLIENT\_CLIENTSECRET
- ARAS\_VAULT\_INNOVATORSERVERURL
- ARAS\_VAULT\_ACCESSCONTROLALLOWORIGIN
- ARAS\_VAULT\_ISPLUGINSTORAGE



- ARAS\_VAULT\_CLOUDSTORAGEPLUGINNAME
- ARAS\_VAULT\_LoggerConfiguration\_\_MinimumLevel
- ARAS\_VAULT\_RedisDataStorage\_\_Enabled
- ARAS\_VAULT\_RedisDataStorage\_\_ConnectionString
- ARAS\_VAULT\_RedisDataStorage\_\_KeyPrefix
- ARAS\_DB\_NAME
- ARAS\_CONVERSION\_USER
- ARAS\_CONVERSION\_LoggerConfiguration\_\_MinimumLevel

