

Public Variables list

The environment-specific configuration functionality available for Aras Enterprise customers working with containerized deployments supports the list of Public Variables. These public variables can be used in transformations without adding a variable to Variable Groups as their values are automatically added during deployment. See the list of supported public variables below:

- ARAS_AGENT_REPLICATION_STATUS
- ARAS_AGENT_REPLICATION_INTERVAL
- ARAS_AGENT_REPLICATION_MAX_BATCH
- ARAS_AGENT_REPLICATION_MAX_PENDING
- ARAS_AGENT_REPLICATION_TIMEOUT
- ARAS_AGENT_REPLICATION_USER
- ARAS_AGENT_LoggerConfiguration__MinimumLevel
- ARAS_AGENT_AgentService__InnovatorServerUrl
- ARAS_INNOVATOR_INSTANCE_NAME
- ARAS_INNOVATOR_CLIENT_ORIGIN
- ARAS_INNOVATOR_CLIENT
- ARAS_INNOVATOR_CLIENT_INTERNAL
- ARAS_INNOVATOR_CLIENT_SERVER
- ARAS_INNOVATOR_DEPLOYMENT_NAME
- ARAS_INNOVATOR_SERVER
- ARAS_INNOVATOR_SERVER_INTERNAL
- ARAS_INNOVATOR_VAULT_SERVER_INTERNAL
- ARAS_INNOVATOR_CONVERSION_SERVER
- ARAS_INNOVATOR_VAULT_SERVER
- ARAS_INNOVATOR_OAUTH_SERVER
- ARAS_INNOVATOR_OAUTH_SERVER_INTERNAL
- ARAS_INNOVATOR_AGENT_SERVICE
- ARAS_INNOVATOR_TRANSIENT_ERROR_NUMBERS
- ARAS_INNOVATOR_SERVER_METHOD_ASSEMBLY_CACHE_EXPIRATION
- ARAS_CLIENT
- ARAS_CLIENT_REDIS_CONNECTION_STRING
- ARAS_CLIENT_REDIS_KEY_PREFIX



- ARAS_CLIENT_DATA_PROTECTION_KEY_LIFETIME
- ARAS_CLIENT_LoggerConfiguration__MinimumLevel
- ARAS_OAUTH_CERTIFICATE_PASSWORD
- ARAS_OAUTH_BASE_PATH
- ARAS_OAUTH_LoggerConfiguration__MinimumLevel
- ARAS_OAUTH_DATA_PROTECTION_KEY_LIFETIME
- ARAS_OAUTH_REDIS_CONNECTION_STRING
- ARAS_OAUTH_REDIS_KeyPrefix
- ARAS_SERVER_MAIL_DELIVERYMETHOD
- ARAS_SERVER_SMTP_SERVER
- ARAS_SERVER_SMTP_PORT
- ARAS_SERVER_SMTP_SSL
- ARAS_SERVER_SMTP_USERNAME
- ARAS_SERVER_SMTP_PASSWORD
- ARAS_SERVER_DATABASES
- ARAS_SERVER_ACCESSCONTROLMAXAGE
- ARAS_SERVER_ACCESSCONTROLEXPOSEHEADERS
- ARAS_SERVER_ACCESSCONTROLALLOWORIGIN
- ARAS_SERVER_INITIALIZE_DATABASES_ON_STARTUP
- ARAS_SERVER_LoggerConfiguration__MinimumLevel
- ARAS_SERVER_Tracing__Instrumentation__SqlClient__Enabled
- ARAS_SERVER_VAULT_REQUEST_TIMEOUT
- ARAS_SERVER_REDIS_CONNECTION_STRING
- ARAS_SERVER_REDIS_KEY_PREFIX
- ARAS_SERVER_REDIS_RETRY_BACKOFF_MILLISECONDS
- ARAS_SERVER_REDIS_PREVENT_THREAD_THEFT
- ARAS_SERVER_DATA_PROTECTION_KEY_LIFETIME
- ARAS_SERVER_INITIALIZE_DATABASES_ON_STARTUP_TIMEOUT_SECONDS
- ARAS_SERVER_REPORT_SERVER
- ARAS_SERVER_MSGRAPHAPICLIENT_TENANTID
- ARAS_SERVER_MSGRAPHAPICLIENT_CLIENTID
- ARAS_SERVER_MSGRAPHAPICLIENT_CLIENTSECRET
- ARAS_VAULT_INNOVATORSERVERURL
- ARAS_VAULT_ACCESSCONTROLALLOWORIGIN
- ARAS_VAULT_ISPLUGINSTORAGE



- ARAS_VAULT_CLOUDSTORAGEPLUGINNAME
- ARAS_VAULT_LoggerConfiguration__MinimumLevel
- ARAS_VAULT_RedisDataStorage__Enabled
- ARAS_VAULT_RedisDataStorage__ConnectionString
- ARAS_VAULT_RedisDataStorage__KeyPrefix
- ARAS_DB_NAME
- ARAS_CONVERSION_USER
- ARAS_CONVERSION_LoggerConfiguration__MinimumLevel

